



| DUCT-FREE MINI-SPLIT SINGLE-ZONE SYSTEMS | | | | | |
|--|---------------------|---------------------|---------------------|---------------------|---------------------|
| STANDARD FEATURES | 18 SEER P Series | 20 SEER R Series | 23 SEER X Series | 27 SEER Y Series | 30 SEER Z Series |
| Automatic Operation | • | • | • | • | • |
| Cooling | • | • | • | • | • |
| Heating | • | • | • | • | • |
| Dehumidification | • | • | • | • | • |
| Fan | • | • | • | • | • |
| Wi-Fi Function | • | • | • | • | • |
| G10 Technology | • | • | • | • | • |
| 1Hz Inverter Technology | • | • | • | • | • |
| Energy-Saving | • | • | • | • | • |
| Sleep Mode | • | • | • | • | • |
| 4-Sleep Curve | • | • | • | • | • |
| 3-Sleep Curve | • | • | • | • | • |
| 3D Auto Swing (Vertical and Horizontal Auto Swing) | • | • | • | • | • |
| Up and Down Swing | • | • | • | • | • |
| Left and Right Swing | • | • | • | • | • |
| Fixed-Angle Swing | • | • | • | • | • |
| 7 Fan Speeds | • | • | • | • | • |
| 4 Fan Speeds | • | • | • | • | • |
| Turbo Cooling & Heating | • | • | • | • | • |
| Quiet | • | • | • | • | • |
| iFeel | • | • | • | • | • |
| Intelligent Preheating | • | • | • | • | • |
| Intelligent Defrosting | • | • | • | • | • |
| Auto-Clean | • | • | • | • | • |
| Dry Anti-Mildew Design | • | • | • | • | • |
| Soft Start | • | • | • | • | • |
| Self Diagnosis | • | • | • | • | • |
| Refrigerant leaking protection | • | • | • | • | • |
| Overload Voltage Protection | • | • | • | • | • |
| Compressor Electric Heater Function | • | • | • | • | • |
| 129°F (54°C) Cooling | • | • | • | • | • |
| 0°F (-18°C) | • | • | • | • | • |
| Low Ambient Cooling | • | • | • | • | • |
| -4°F (-20°C) | • | • | • | • | • |
| Low Ambient Heating | • | • | • | • | • |
| 2-Stage Compressor | • | • | • | • | • |
| Timer | • | • | • | • | • |
| Temperature | • | • | • | • | • |
| Auto Restart | • | • | • | • | • |
| Lock | • | • | • | • | • |
| LED | • | • | • | • | • |
| Indoor Unit Matching for one-to-one and multi-zone | • | • | • | • | • |
| Ultra-Thin Design | • | • | • | • | • |
| Double-Sided Drainage | • | • | • | • | • |

| DUCT-FREE MINI-SPLIT SINGLE-ZONE SYSTEMS | | | | | |
|--|---------------------|---------------------|---------------------|---------------------|---------------------|
| OPTIONAL FEATURES | 18 SEER P Series | 20 SEER R Series | 23 SEER X Series | 27 SEER Y Series | 30 SEER Z Series |
| Wired Controller | • | • | • | • | • |
| Central Controller | • | • | • | • | • |
| Wi-Fi Function | • | • | • | • | • |
| Photo-Catalyst Filter | • | • | • | • | • |
| Active Carbon Filter | • | • | • | • | • |

P SERIES 18 SEER SINGLE-ZONE S

115V 9K-12K BTU/h INVERTER HE/ COOLING ONLY & WALL-MOUNT I

The slim and stylish 18 SEER Inverter Heat Pump system is built to last and offers intelligent contr

Key Features

- High-efficiency inverter technology
- Auto swing (vertical)
- Multiple fan speeds
- Low ambient cooling to 0° F

| P SERIES SYSTEM MODELS | | |
|----------------------------------|-----------------------------------|----------|
| Rated Performance | System Type | |
| | Rated Cooling Capacity | BTU/h |
| | Cooling Capacity (Min-Max) | BTU/h |
| | Rated Heating Capacity | BTU/h |
| | Heating Capacity (Min-Max) | BTU/h |
| | EER | |
| | SEER | |
| Electrical Data | HSPF | |
| | Rated Voltage | V-PH-Hz |
| | Rated Cooling Current | Amps |
| | Rated Heating Current | Amps |
| MCA | Amps | |
| MOC | Amps | |
| Indoor Wall-Mount Unit | Indoor Model Number | |
| | Set Temperature Range | °F (°C) |
| | Airflow High to Low | CFM |
| | Sound Pressure Level High to Low | dB(A) |
| | Unit Dimension (WxHxD) | in. (mm) |
| Net / Gross Weight | lbs (kg) | |
| Outdoor Unit | Outdoor Model Number | |
| | Operation Range - Cooling | °F (°C) |
| | Operation Range - Heating | °F (°C) |
| | Refrigerant | |
| | Refrigerant Charge | oz (kg) |
| | Unit Dimension (WxHxD) | in. (mm) |
| Net / Gross Weight | lbs (kg) | |
| Sound Pressure Level dB(A) | dB(A) | |
| Piping | Max. Total Piping Length | ft. (m) |
| | Max. Total Piping Height | ft. (m) |
| | Piping Connection - Liquid (O.D.) | in. |
| | Piping Connection - Gas (O.D.) | in. |
| Piping Connection - Drain (O.D.) | in. | |

Please refer to Product submittals for gas/liquid line port sizes
 Test conditions are based on ASHRAE 90.1-2010 (4.1). Rating conditions (cooling)- Indoor: D.B. 82° F, W.B. 67° F (28° C, 19° C); (heating)- Indoor: D.B. 70° F (21° C), W.B. 60° F (16° C); Outdoor: D.B. 47° F (8° C), W.B. 32° F (0° C). Specifications are subject to change without notice. Manufacturer reserves the right to discontinue products without notice.